


**DESCRIPTION:**

1. DO Galvanic, Ø12mm x109mm, Black ABS, Ø3.8mm Pt disc in glass Cathode, Pt1000 in glass tube, Lead Tube Anode, 10 Ft COAX+4 Cable, tinned wire, 1mil Membrane module.

2. Output with 7.5k ohm shunt resistor:  
 In air saturated DI water:  $30 \pm 10 \text{mV}$  (@25°C)  
 In Oxygen free water:  $\leq 1 \text{mV}$  (@25°C)

3. Concentration range: 0-20 mg/L  
 4. Temperature Range: 0-80°C  
 5. TC Element: Pt1000



Membrane Module

所有表面粗糙度级别

**A**

除特别注明之外

图纸中的信息仅为傲乐科学仪器（上海）有限公司所有。没有傲乐的书面允许说明，严禁复制。

无特别说明图上标注的是公制尺寸【mm】

设计			傲乐科学仪器（上海）有限公司	
绘图	ERIC	07-01-2013		
审核			DO Galvanic, 12mm x109mm, Black ABS, Ø0.195" Pt disc in glass Cathode, Pt1000 in glass tube, Lead Tube Anode, 10 Ft COAX+4 Cable, tinned wire, 1mil Membrane module.	
批准				
材料:				
名称:	FINAL PRODUCT		图纸号:	型号: DOG2-Axxxx
			客户编号:	SHEET OF

如果你不了解图纸上的有关要求，请停下来，并尽快接触工程部门。